

30.09.11

Pitched roof cabins	Size	Price ex VAT		Price inc. VAT	
		45 mm	70 mm	45 mm	70 mm
Nordic 4232	3.20 x 4.20	£ 2,930	£ 3,480	£ 3,516	£ 4,176
Nordic 4242	4.20 x 4.20	£ 3,540	£ 4,102	£ 4,248	£ 4,922
Nordic 5242	5.20 x 4.20	£ 4,050	£ 4,962	£ 4,860	£ 5,954
Nordic 5050	5.00 x 5.00	£ 4,510	£ 5,580	£ 5,412	£ 6,696
Nordic 6232S	6.20 x 3.20	£ 4,430	£ 5,405	£ 5,316	£ 6,486

Pent roof cabins	Size	45 mm	70 mm	45 mm	70 mm
Nordic 4232F	4.20 x 3.20	£ 2,930	£ 3,585	£ 3,516	£ 4,302
Nordic 4240F	4.20 x 4.20	£ 3,540	£ 4,302	£ 4,248	£ 5,162
Nordic 6242FS	5.20 x 4.20	£ 4,430	£ 5,471	£ 5,316	£ 6,565
Nordic 7542FS	7.50 x 4.20	£ 5,665	£ 6,940	£ 6,798	£ 8,328

Price for upgrade:		Price ex VAT	Price inc. VAT
Insulated floor	per sq. m floor	£26	£31
Insulated roof	per sq. m roof	£24	£29
Wall insulation	per sq. m wall	£26	£31
Isola shingles	per sq. m roof	£9	£11
Cedar shingles	per sq. m roof	£20	£24
Decking & Terrace	per sq. m decking	£22	£26
1000W NOBO skirting heater	pcs	£148	£178
Care Heat Pump 5 kw	pcs fitted	£945	£992
Doors and windows upgrade	see separate list.		

Included supply of standard cabin

45 mm or 70 mm pine wall logs log height 130 mm
 Single or double roof beams 45 mm or 70 mm
 Pine tongue & groove ceiling boards 19 mm x 125 mm
 Fascias (gable and eaves) 16 mm x 100 mm
 Roofing felt shingles (black, red or green) pack of 3.0 sq.m for pitched roofs
 Vulcanised rubber sheet for pent roofs
 Inside ceiling coving 16 mm x 40 mm
 Foundation frame treated timber
 Floor joists for concrete slab 2" x 2"
 Pine floor boards tongue & groove 28 mm x 125 mm
 Skirting board 16 mm x 40 mm
 Doors with architraves as specified in drawing with handles and locks
 Windows with architraves as specified in drawing with handles
 Clear protecting floor varnish (matt, gloss or semi-gloss) included with insulated floor upgrade
 One external coat in colour of choice included with insulated floor and roof upgrade

Nordic Upgrade alternatives.

Windows and doors

We have a wide range of windows and doors for the cabins. The standard delivery of windows is specified under each cabin drawing. All our cabins comes with 24mm insulation glass. You can however change these windows and doors, and you find the alternatives in our price list which also gives you dimensions.

Insulated roof upgrade

Insulation of the roof is beneficial for both keeping the heat inside and to screen of heat from the sun. The insulated roof is normally built on top of the standard roof and will require following extra materials: Damp-membrane, 4" roof joists, 100 mm insulation material, 19 mm Water resistant cyber board. For cabins under permitted rights and to a maximum of 2.5m height, it might be necessary to build the roof from below and insulate between the beams. Our roof upgrade includes roof shingles for the pitched roof and vulcanised rubber sheeting for the pent roof.

Insulated floor upgrade

Insulation in floor is for creating a comfortable floor and limit any draft and/or humidity coming off ground. The insulated floor is built with a sub-floor between 5" joists with 100 mm insulation and damp-membrane under the pine floor. An insulated floor will require an extra wall log under the doors to fit the height of the joists.

Wall insulation upgrade

If you want to improve insulation for all year living we can offer a wall insulation pack which involves supply of wall studs, damp membrane, insulation material and a tongue & groove cladding or boards as internal wall. Contact us for more information if this is required for your project.

Roof cover upgrade

A variation of roofs can be supplied. The standard felt roof can be upgraded to ISOLA shingles, cedar shingles, vulcanised rubber roof for pent roofs and tiles, all subject to separate quote.

Decking and terraces

We can add decking and terraces to your log cabin, just give us your measurements and we will add this materials to your purchase order.

Wood Treatment alternatives

You can order a range of special Norwegian wood treatments from us. See price list and separate information brochure.

Heating of your cabin

Depending of the size of your cabin we can provide electric skirting heaters, reversible heat pumps and even log burners. Just contact us for information and various prices.

NOTES

Single beams are used where the roof span is less than 4 meter. Standard beams are based on same dimension as the wall logs. Directions of beams are from gable to gable on a pitched roof and the shortest distance on a pent roof or flat roof.

Foundation frame is supplied in pressure treated timber to create a water protected frame between wall logs and the ground/foundation.

IMPORTANT

Please be reminded that timber is a natural product. It will have imperfections, cracks, warping and knot holes and knots. Also these products are supplied flat-packed for adult assembly (need two people). All timber need to be maintained and we recommend that you as soon as possible after installation make sure external surfaces is stained or painted with appropriate quality wood treatments. Since both doors and windows comes untreated it is very important that they are treated as soon as possible both internally and